

SilentMaster 210-8-6 WOF A313000

Product specification sheet



Image.: Typ SEM 210-8-6 WOF

Technical Data	A313000
Air displacement	210 l/min
Max. free air delivery	120 l/min
Max. pressure	6/8 bar
Cylinder/Stage	1/1
Tank capacity	6 l
Voltage	230 Volt/50 Hz
Motor output	1,1 kW
Drive	2.850 min ⁻¹
Sound power level	85 dB(A)
Sound pressure level	65 dB (A)
Dimensions (WxDxH)	600x270x570 mm
Weight	23 Kg

Product description

Fact Sheet

- Low noise, oilfree, mobile and portable one cylinder piston compressor with direct drive motor
- For applications up to 8 bar
- Due to the special soundproof enclosure the compressor operates virtually silent and can be used in the workplace
- Equipped with pressure reducer, two pressure gauges for measuring tank and outlet pressure and a quick release coupling to connect up the air supply
- Applications: smaller sized staple and nail guns, blow out guns, cartridge guns, grease guns and rivet guns

SilentMaster 210-8-6 WOF A313000

Product specification sheet



Compact and handy in size with integrated handles and two wheels for easy transportation

Precise working due to two pressure gauges for measuring the tank and outlet pressure

Easy access and operation due to centrally fitted pressure reducer and quick release coupling

Best protection of the components due to the plastic housing



Virtually silent because compressor is equipped with soundproof enclosure

Oilfree aggregate is very **low-maintenance**

Easy service & maintenance because discharge port is outside of the housing

Long service life thanks to the 10 years anti-corrosion warranty on the compressed air tank

Further information

Operates fully automatically

Unloader pressure switch and motor protection

Scope of delivery

Instruction manual

Warranty

12 months for industrial use
24 months for private (non-commercial) use
36 months when registered online